




ELECTRIC TRICKLE DUSTERS

OVERVIEW:

The Matrix trickle duster, available in 400 and 1,000 lb. capacity, fluidizes through a steel manifold instead of an air pad. The motor is directly coupled to the blower, which eliminates belt problems. This duster is one of the simplest to operate and maintain.

FEATURES / SPECIFICATIONS:


- Direct drive 5 hp 480V or 575V
- In-tank steel manifold for fluidization (No air pad)
- Up to 10 lbs/min of dust through 400' of 2" hose
- Check valve protection for blower
- Model 33 Roots style blower with air filter
- Skid (Wheels can be optional)
- 28" skid-mounted frame height
- 56" long x 30" wide
- Weight: Approx. 500 lbs.
- Matrix service and support
- Delivery included in price



*Matrix Design Group
is an authorized distributor
of CBS Equipment*

www.matrixteam.com 

Phone: 812.490.1525 • Fax: 812.490.1582 • 3299 Tower Drive • Newburgh, Indiana 47630 • email: sales@matrixteam.com



“OEM” SCOOP FLINGER DUSTER

OVERVIEW / ORDERING:

Bucket duster parts will interchange with most manufacturers / brands.

If available when ordering, please specify:

1. Model of the scoop
2. Outside width of bucket
3. Distance between bottom of ram and floor of bucket when the blade is extended

FEATURES / SPECIFICATIONS:

- Width: 110” – 120”
- Height: 15”
- Weight: 2,000 Lbs. (Approx.)
- Hydraulics: 12-15 GPM @ 1,000 -1,500 PSI
- Matrix service and support



*Matrix Design Group
is an authorized distributor
of CBS Equipment*

www.matrixteam.com 

Phone: 812.490.1525 • Fax: 812.490.1582 • 3299 Tower Drive • Newburgh, Indiana 47630 • email: sales@matrixteam.com